

POOL MINI 12V/24V DC




The Ground series was designed using modern simulation methods in order to obtain the highest product quality.

- based on CREE® LEDs
- IP67
- made of 316L steel
- also available with an square front
- 5-year warranty
- 3,5 W



Working temperature range	-20°C ÷ +55°C
IP protection class	IP68
Lifetime L80B10	≥ 60 000h
Impact resistance	IK10
Protection class	III
Connection	1,5m
Wiring	SIHF 2X1.5
Dimming	ON-OFF/PWM
Luminous flux tolerance	±10%
Angle of distribution	15°, 27°, 43°

TECHNICAL DRAWINGS



POOL MINI 12V/24V DC




Niviss swimming pool luminaires can be immersed up to a depth of 3 meters and used to light and illuminate :

- swimming pools
- fountains

ELECTRICAL INSTALLATION

Connecting to the power supply should be done when the power supply is off.



ORDER CODE AND TECHNICAL SPECIFICATIONS OF VARIANTS

VARIANT CODES IN THE TABLE BELOW TECHNICAL SPECIFICATIONS OF VARIANTS IN DATASHEET OF VARIANT

GENERAL TERMS OF USE

- Before using a luminaire, make sure what voltage range it is designed to.
- Connecting to the power supply should be done when the power supply is off.
- Use appropriate sockets and plugs: Ensure that your electrical sockets and plugs are compatible with the lamp's voltage and plug type.
- Use appropriate wiring for luminaires.
- Avoid overloading electrical circuits by not connecting too many lamps to a single outlet or circuit. Check the condition of the power cord and plug for any signs of damage or wear.
- Pay attention to the correct polarity when connecting the luminaires. Incorrect polarity may prevent the luminaires from functioning properly or could potentially damage them.
- Installation of the luminaires should be done by qualified person.
- Keep your luminaires clean and free from dust and debris, as it can affect their performance.
- Follow the luminaire connection diagram above.
- Avoid direct exposure of bright light sources to your eyes. Position luminaires in a way that minimizes direct glare or uncomfortable brightness.
- Ensure that the luminaire is placed on a stable surface and kept away from flammable materials. Allow sufficient clearance around the luminaire to prevent overheating.
- Keep away from fire.

ENVIRONMENTAL CAUTION!

It is prohibited to dispose of obsolete and waste electrical and electronic equipment together with regular household wastes. They should be properly sorted and recycled. Old electrical and electronic equipment should be returned to a waste collection point established by a waste-management service. Waste electrical and electronic equipment can be broken down to base materials and then recycled. For more information regarding waste management please contact your local authorities, waste-management service or the seller of electrical and electronic devices.

ORDER CODE AND TECHNICAL SPECIFICATIONS OF VARIANTS

Index	IP protection class	[DEG]	[K]	Lumen Output [lm]	CRI/RA	[W]	Power supply type	Body material	Front material	EAN	Front shape
POOL-MINI-3-WW-15-RD-SS-LV-R	IP68	15	3000	215	≥80	3.5	12V/24V DC	SST	SST	5905658701765	○
POOL-MINI-3-WW-27-RD-SS-LV-R	IP68	27	3000	215	≥80	3.5	12V/24V DC	SST	SST	5905658701772	○
POOL-MINI-3-VW-15-RD-SS-LV-R	IP68	15	2700	195	≥80	3.5	12V/24V DC	SST	SST	5905658701703	○
POOL-MINI-3-VW-27-RD-SS-LV-R	IP68	27	2700	195	≥80	3.5	12V/24V DC	SST	SST	5905658701710	○
POOL-MINI-3-NW-43-RD-SS-LV-R	IP68	43	4000	215	≥80	3.5	12V/24V DC	SST	SST	5905658701840	○
POOL-MINI-3-NW-27-RD-SS-LV-R	IP68	27	4000	215	≥80	3.5	12V/24V DC	SST	SST	5905658701833	○
POOL-MINI-3-VW-43-RD-SS-LV-R	IP68	43	2700	195	≥80	3.5	12V/24V DC	SST	SST	5905658701727	○
POOL-MINI-3-CW-15-RD-SS-LV-R	IP68	15	5000	230	≥80	3.5	12V/24V DC	SST	SST	5905658701888	○
POOL-MINI-3-CW-27-RD-SS-LV-R	IP68	27	5000	230	≥80	3.5	12V/24V DC	SST	SST	5905658701895	○
POOL-MINI-3-WW-43-RD-SS-LV-R	IP68	43	3000	215	≥80	3.5	12V/24V DC	SST	SST	5905658701789	○
POOL-MINI-3-NW-15-RD-SS-LV-R	IP68	15	4000	215	≥80	3.5	12V/24V DC	SST	SST	5905658701826	○
POOL-MINI-3-CW-43-RD-SS-LV-R	IP68	43	5000	230	≥80	3.5	12V/24V DC	SST	SST	5905658701901	○